

Filter / Softener Control Valves



4m³/h
Model:F67P1



10m³/h
Model:75



20m³/h
Model:F95



30m³/h
Model:F112

Automatic Filter Valves For Water Treatment Systems (LED Display)

Product Technical Parameter

Model	Inlet/Outlet	Drain	Base & Riser Pipe	Max Flow Rate	Tank Dia Range	Remark
F67P1	DN25-1	DN25-1	DN25-1	4M3/hr	9"-14"	Top Mounted
F75	DN50-2"	DN50-2"	DN50-2"	10M3/hr	16"~24"	Side Mounted
F95	DN50-2"	DN50-2"	DN50-2"	20M3/hr	20"~36"	Side Mounted
F112	DN65-2.5"	DN65-2.5"	DN80-3"	30M3/hr	24"~48"	Side Mounted

Structure Features

- ★ Piston structure.
- ★ Indication of long time power cut, data saved after power off (Saved for three days).
- ★ No hard water bypass in rising cycle.
- ★ Remote handling connector b-01(02).
- ★ Backwash, fast rinse frequencies setting, services one time, backwash and fast rinse several times.
- ★ Remote signal input connector.
- ★ Interlock function for contemporary system and individual rising.
- ★ Start rising by days or hours.
- ★ Options available for filter timer control, filter meter control, softener timer control and softener meter control